

SECTION I—CLAIMS

Amendment to the Claims:

This listing of the claims will replace all prior versions and listings of claims in the application. Claims 1-46 are amended herein. No claims are canceled. No new claims are introduced. Claims 1-46 remain pending in the application.

Listing of Claims:

1. (Currently amended) A method for processing a group of instructions, the method comprising:
~~processing a group of instructions in topological dependence order;~~
selecting an instruction to schedule, the instruction associated with ~~an~~ at least one operand,
wherein the operand comprises a live range representing the operational duration of the
operand relative to the group of instructions being processed;
~~to schedule; allocating a register to one or more of the operands; determining if the live range of~~
~~the operand spans a function call; if so,~~
attempting to allocate a preserved register to the operand for its live range when its live range
spans a function call; if not,
attempting to allocate a scratch register to the operand for its live range when its live range does
not span the function call; and
~~if the determination is unknown, treating the live range as tentative; and if the allocation was~~
~~successful,~~
scheduling the instruction when the allocation of the preserved register or the scratch register is
successful.
2. (Currently amended) The method of claim 1, further comprising:

~~wherein allocating a register to one or more of the operand includes: determining if the operand's~~
~~use begins a live range or ends a live range; if the operand's use begins a live range,~~
~~attempting to allocate a register;~~
~~terminating the attempt to allocate the preserved register or the scratch register to the operand for~~
~~its live range when~~ if the operand's use by the selected instruction falls at the end of the
~~ends a live range; and~~ [[,]]
marking the preserved register or the scratch register ~~associated~~ allocated to with the operand as
available for reallocation.

3. (Currently amended) The method of claim 1, wherein attempting to allocate a the preserved
register ~~includes~~ comprises:

~~determining if a preserved register is available for allocation from a list of previously used~~
~~preserved registers; and if so,~~
allocating the ~~available~~ preserved register to the operand for its ~~for the~~ live range ~~defined by the~~
~~operand~~ when the preserved register is in a list of previously used preserved registers
marked as available for allocation.

4. (Currently amended) The method of claim 3, further ~~including~~ comprising:

~~if a preserved register is not available from the list of previously used preserved registers,~~
attempting to find a ~~tentative live range that includes a~~ second preserved register ~~that is in the list~~
~~of previously used preserved registers and currently allocated to a tentative live range of a~~
~~second operand; and if successful,~~
reallocating the second ~~this~~ preserved register ~~for~~ to the operand for its ~~the~~ live range ~~defined by~~
~~the operand,~~ and reserving a different preserved register ~~for~~ to the second operand for its
~~the~~ tentative live range when the attempt to find the second preserved register allocated to

the second operand for its tentative live range is successful.

5. (Currently amended) The method of claim 4, further ~~including~~ comprising
~~, if the attempt to find a tentative live range that includes a preserved register that is in the list is~~
~~not successful,~~

adding a new preserved register to the list of previously used preserved registers; and
allocating ~~this~~ the new preserved register to the operand for its ~~the~~ live range ~~defined by the~~
~~operand~~ when the attempt to find the second preserved register allocated to the second
operand for its tentative live range fails.

6. (Currently amended) The method of claim 1, wherein attempting to allocate ~~[[a]]~~ the scratch
register to the operand for its live range ~~includes~~ comprises:
~~determining if a scratch register is available for allocation; if so, allocating a scratch register for~~
~~the live range defined by the operand; if not,~~
attempting to ~~steal~~ deallocate a second scratch register from a tentative live range of a second
operand live range when the attempt to allocate the scratch register to the operand for its
live range fails ~~marked as tentative; determining if the attempted theft was successful; if~~
~~so,~~

allocating the ~~stolen~~ second scratch register to the operand for its live range ~~defined by the~~
~~operand~~ when the second scratch register is successfully deallocated from the second
operand for its tentative live range; and if not,
attempting to allocate a the preserved register to the operand for its live range when the attempt
to deallocate the second scratch register from the second operand for its tentative live
range fails.

7. (Currently amended) The method of claim 1, further comprising:

marking the live range of the operand as a tentative live range when current information about the live range is insufficient to determine whether or not the live range spans the function call;

~~wherein treating the live range as tentative further includes: if both a scratch register and a preserved register are available for allocation, reserving~~
pre-allocating both the scratch register and the preserved register to the operand for its tentative live range;

processing one or more additional instructions ~~allowing another instruction to be processed;~~ and
waiting for ~~more~~ additional information about the tentative live range.

8. (Currently amended) The method of claim 7, further comprising:

~~including, when more information is available: if the last use of the live range has been scheduled,~~

receiving the additional information about the tentative live range;

~~allocating the reserved scratch register to the live range defined by the operand, and freeing~~
deallocating the reserved preserved register from the operand for its tentative live range when the last use of the operand for its tentative live range has been scheduled; and

~~if a function call has been scheduled before the last use of the live range or the reserved scratch register has been stolen, allocating the preserved register to the live range defined by the operand and freeing~~

deallocating the reserved scratch register from the operand for its tentative live range when the function call is scheduled before the last use of the operand for its tentative live range or when the scratch register is reallocated by any other process.

9. (Currently amended) The method of claim 7, ~~wherein~~ further comprising:

~~reserving a preserved register for the tentative live range includes: preferring to reserve~~
~~attempting to allocate~~ a currently unused preserved register ~~that is in the list of previously used~~
~~preserved registers to the operand for its tentative live range;[[,]] and before~~
~~attempting to allocate~~ ~~reserving~~ a new unused preserved register ~~to the operand~~ for the ~~its~~
tentative live range when the attempt to allocate the currently unused preserved register
to the operand for its tentative live range fails.

10. (Currently amended) The method of claim [[9]] 7, further comprising:

~~wherein treating the live range as tentative further includes: if a scratch register is not available~~
~~for allocation,~~

attempting to allocate a the preserved register to the operand for its tentative live range when the
scratch register is determined to be unavailable.

11. (Currently amended) The method of claim 1, further comprising:

~~wherein allocating a register to at least one or more of operands associated with the instruction~~
~~includes: if no proper registers are available for allocation,~~

inserting a register spill when the attempt to allocate the preserved register and the attempt to
allocate the scratch register to the operand for its live range both fail; and

either re-attempting to allocate the preserved register and the scratch register to the operand for
its live range, a register, or selecting ~~another~~ a second instruction to schedule.

12. (Currently amended) An article of manufacture comprising[[:]] a machine readable medium

having ~~a plurality of machine accessible instructions~~ logic thereon that, wherein ~~when the~~
~~instructions are executed, the instructions provide~~ logic provides for processing a group
of instructions, the logic further providing for:

~~processing a group of instructions in topological dependence order;~~

selecting an instruction to schedule, the instruction associated with an ~~at least one~~ operand,
wherein the operand comprises a live range representing the operational duration of the
operand relative to the group of instructions being processed;
~~to schedule; allocating a register to one or more of the operands; determining if the live range of~~
~~the operand spans a function call; if so,~~
attempting to allocate a preserved register to the operand for its live range when its live range
spans a function call; if not,
attempting to allocate a scratch register to the operand for its live range when its live range does
not span the function call; and
~~if the determination is unknown, treating the live range as tentative; and if the allocation was~~
~~successful,~~
scheduling the instruction when the allocation of the preserved register or the scratch register is
successful.

13. (Currently amended) The article of manufacture of claim 12, ~~wherein the instructions~~
~~providing for allocating a register to one or more of the operand includes the logic~~
~~instructions further providing for:~~
~~determining if the operand's use begins a live range or ends a live range; if the operand's use~~
~~begins a live range, attempting to allocate a register;~~
terminating the attempt to allocate the preserved register or the scratch register to the operand for
its live range when ~~if~~ the operand's use by the selected instruction falls at the end of the
ends a live range; and ~~[[,]]~~
marking the preserved register or the scratch register ~~associated~~ allocated to ~~with~~ the operand as
available for reallocation.

14. (Currently amended) The article of manufacture of claim 12, wherein the logic instructions providing for attempting to allocate a the preserved register comprises includes instructions providing for:
~~determining if a preserved register is available for allocation from a list of previously used preserved registers; and if so,~~
allocating the ~~available~~ preserved register to the operand for its ~~for the~~ live range ~~defined by the operand~~ when the preserved register is in a list of previously used preserved registers marked as available for allocation.

15. (Currently amended) The article of manufacture of claim 14, the logic further ~~including~~ instructions providing for:
~~, if a preserved register is not available from the list of previously used preserved registers,~~
attempting to find a ~~tentative live range that includes a~~ second preserved register ~~that is in the list of previously used preserved registers and currently allocated to a tentative live range of a~~ second operand; and if successful,
reallocating the second ~~this~~ preserved register ~~for to the operand for its~~ the live range ~~defined by the operand,~~ and reserving a different preserved register ~~for to the second operand for its~~ the tentative live range when the attempt to find the second preserved register allocated to the second operand for its tentative live range is successful.

16. (Currently amended) The article of manufacture of claim 15, ~~further including the logic~~ instructions further providing for:
~~, if the attempt to find a tentative live range that includes a preserved register that is in the list is not successful,~~
adding a new preserved register to the list of previously used preserved registers; and

allocating ~~this~~ the new preserved register to the operand for its ~~the live range defined by the operand~~ when the attempt to find the second preserved register allocated to the second operand for its tentative live range fails.

17. (Currently amended) The article of manufacture of claim 12, wherein the logic instructions providing for attempting to allocate ~~[[a]]~~ the scratch register to the operand for its live range comprises:

~~includes instructions providing for: determining if a scratch register is available for allocation; if~~

~~so, allocating a scratch register for the live range defined by the operand; if not,~~

attempting to ~~steal~~ deallocate a second scratch register from a tentative live range of a second

operand live range when the attempt to allocate the scratch register to the operand for its

live range fails ~~marked as tentative; determining if the attempted theft was successful; if~~

~~so,~~

allocating the ~~stolen~~ second scratch register to the operand for its live range defined by the

~~operand~~ when the second scratch register is successfully deallocated from the second

operand for its tentative live range; and if not,

attempting to allocate ~~a~~ the preserved register to the operand for its live range when the attempt

to deallocate the second scratch register from the second operand for its tentative live

range fails.

18. (Currently amended) The article of claim 12, ~~wherein~~ the logic instructions further providing for:

marking ~~treating~~ the live range of the operand as a tentative live range when current information

about the live range is insufficient to determine whether or not the live range spans the

function call;

~~further includes instructions providing for: if both a scratch register and a preserved register are available for allocation, reserving~~
~~pre-allocating both the scratch register and the preserved register to the operand for its tentative live range;~~
~~processing one or more additional instructions allowing another instruction to be processed; and~~
~~waiting for more additional information about the tentative live range.~~

19. (Currently amended) The article of manufacture of claim 18, ~~further including the logic instructions further~~ providing for:
~~, when more information is available: if the last use of the live range has been scheduled,~~
~~receiving the additional information about the tentative live range;~~
~~allocating the reserved scratch register to the live range defined by the operand, and freeing~~
~~deallocating the reserved preserved register from the operand for its tentative live range when the~~
~~last use of the operand for its tentative live range has been scheduled; and~~
~~if a function call has been scheduled before the last use of the live range or the reserved scratch register has been stolen, allocating the preserved register to the live range defined by the operand and freeing~~
~~deallocating the reserved scratch register from the operand for its tentative live range when the~~
~~function call is scheduled before the last use of the operand for its tentative live range or~~
~~when the scratch register is reallocated by any other process.~~

20. (Currently amended) The article of manufacture of claim 18, ~~wherein the logic instructions~~
~~further~~ providing for:
~~reserving a preserved register for the tentative live range includes instructions providing for:~~
~~preferring to reserve~~

~~attempting to allocate a currently unused preserved register that is in the list of previously used~~
~~preserved registers to the operand for its tentative live range;[[,]] and before~~
~~attempting to allocate reserving a new unused preserved register to the operand for the its~~
~~tentative live range when the attempt to allocate the currently unused preserved register~~
~~to the operand for its tentative live range fails.~~

21. (Currently amended) The article of manufacture of claim [[20]] 18, ~~wherein~~ the logic
instructions further providing for:

~~treating the live range as tentative further includes instructions providing for: if a scratch register~~
~~is not available for allocation,~~

~~attempting to allocate a the preserved register to the operand for its tentative live range when the~~
~~scratch register is determined to be unavailable.~~

22. (Currently amended) The article of manufacture of claim 12, ~~wherein~~ the logic instructions
further providing for:

~~allocating a register to at least one or more of operands associated with the instruction includes~~
~~instructions providing for: if no proper registers are available for allocation,~~

~~inserting a register spill when the attempt to allocate the preserved register and the attempt to~~
~~allocate the scratch register to the operand for its live range both fail; and~~

~~either re-attempting to allocate the preserved register and the scratch register to the operand for~~
~~its live range, a register, or selecting another a second instruction to schedule.~~

23. (Currently amended) An apparatus comprising:

~~an instruction scheduler to[[:]] process a group of instructions, the instruction scheduler to~~

~~further in topological dependence order, and select an instruction to schedule, the~~

~~instruction associated with an at least one operand, to schedule the operand comprising a~~

live range to represent the operational duration of the operand relative to the group of instructions to be processed; and
~~schedule an instruction, if the register allocation was successful; and~~
~~a register allocator to~~[[,]] allocate register to a live range associated with one or more operand,
~~determine if the live range of the operand spans a function call, if so, attempt to allocate a~~
~~preserved register to the operand for its live range when its live range spans a function~~
~~call~~[[,]] and if not, attempt to allocate a scratch register to the operand for its live range
when its live range does not span the function call.

~~[[,]] and if the determination is unknown, treat the live range as tentative.~~

24. (Currently amended) The apparatus of claim 23, wherein the register allocator to further
~~is capable of: determining if the operand's use begins a live range or ends a live range; if the~~
~~operand's use begins a live range, attempting to allocate a register;~~
terminate the attempt to allocate the preserved register or the scratch register to the operand for
its live range when if the operand's use by the selected instruction is to fall at the end of
the ends a live range, and
mark marking the preserved register or the scratch register associated to be allocated to with the
operand as available for reallocation.

25. (Currently amended) The apparatus of claim 23, wherein the register allocator to further
~~is capable of, when attempting to allocate a preserved register: determining if a preserved~~
~~register is available for allocation from a list of previously used preserved registers; and if~~
~~so, allocating~~
allocate the available preserved register to the operand for its for the live range defined by the
operand when the preserved register is in a list of previously used preserved registers to

be marked as available for allocation.

26. (Currently amended) The apparatus of claim 25, wherein the register allocator to further
~~is capable of, if a preserved register is not available from the list of previously used preserved~~
~~registers: attempting~~
attempt to find a tentative live range that includes a second preserved register that is in the list of
previously used preserved registers to be allocated to a tentative live range of a second
operand,[[;]] and if successful, allocating
reallocate the second this preserved register for to the operand for its the live range, defined by
the operand, and
reserve reserving a different preserved register for to the second operand for its the tentative live
range when the attempt to find the second preserved register allocated to the second
operand for its tentative live range is successful.

27. (Currently amended) The apparatus of claim 26, wherein the register allocator to further
~~is capable of, if the attempt to find a tentative live range that includes a preserved register that is~~
~~in the list is not successful: adding~~
add a new preserved register to the list of previously used preserved registers[[;]] and allocating
this
allocate the new preserved register to the operand for its the live range defined by the operand
when the attempt to find the second preserved register allocated to the second operand for
its tentative live range fails.

28. (Currently amended) The apparatus of claim 23, wherein the ~~register allocator is capable of,~~
~~when attempting~~ attempt to allocate [[a]] the scratch register to the operand for its live
range comprises the register allocator to further:

determining if a scratch register is available for allocation; if so, allocating a scratch register for the live range defined by the operand; if not, attempting attempt to steal deallocate a second scratch register from a tentative live range of a second operand live range when the attempt to allocate the scratch register to the operand for its live range fails, marked as tentative; determining if the attempted theft was successful; if so, allocating allocate the stolen second scratch register to the operand for its live range defined by the operand when the second scratch register is successfully deallocated from the second operand for its tentative live range,[[;]] and if not, attempting attempt to allocate [[a]] the preserved register to the operand for its live range when the attempt to deallocate the second scratch register from the second operand for its tentative live range fails.

29. (Currently amended) The apparatus of claim 23, wherein the register allocator to further is capable of, when treating a live range as tentative: if both a scratch register and a preserved register are available for allocation, reserving pre-allocate both the scratch register and the preserved register to the operand for its tentative live range,[[;]] process one or more additional instructions, allowing another instruction to be processed; and wait waiting for more additional information about the tentative live range.

30. (Currently amended) The apparatus of claim 29, wherein the register allocator to further is capable of, when more information is available: if the last use of the live range has been scheduled, receive the additional information about the tentative live range, allocating the reserved scratch

~~register to the live range defined by the operand, and freeing~~
deallocate the reserved preserved register from the operand for its tentative live range when the
last use of the operand for its tentative live range has been scheduled,[[;]] and if a
~~function call has been scheduled before the last use of the live range or the reserved~~
~~scratch register has been stolen, allocating the preserved register to the live range defined~~
~~by the operand and freeing~~
deallocate the reserved scratch register from the operand for its tentative live range when the
function call is scheduled before the last use of the operand for its tentative live range or
when the scratch register is reallocated by any other process.

31. (Currently amended) The apparatus of claim 30, wherein the register allocator to further
~~is capable of, when reserving a preserved register for the tentative live range preferring to reserve~~
attempt to allocate an [[a]] currently unused preserved register that is in the list of previously
used preserved registers to the operand for its tentative live range, and before
attempt to allocate reserving a new unused preserved register to the operand for the its tentative
live range when the attempt to allocate the unused preserved register to the operand for
its tentative live range fails.

32. (Currently amended) The apparatus of claim [[31]] 29, wherein the register allocator to
further
~~is capable of, when treating a live range as tentative: if a scratch register is not available for~~
~~allocation, attempting~~
attempt to allocate [[a]] the preserved register to the operand for its tentative live range when the
scratch register is determined to be unavailable.

33. (Currently amended) The apparatus of claim 23, the register allocator to further

~~is capable of: if no proper registers are available for allocation, inserting~~
insert a register spill when the attempt to allocate the preserved register and the attempt to
allocate the scratch register to the operand for its live range both fail,[[;]] and
~~either re-attempting re-attempt~~ to allocate the preserved register and the scratch register to the
operand for its live range, a register, or selecting another select a second instruction to
schedule.

34. (Currently amended) The apparatus of claim 23, wherein the register allocator further
comprises includes:

a scratch register allocator to allocate scratch registers to operands for their live ranges when the
live ranges ~~that~~ do not span a function call;

a preserved register allocator to allocate preserved registers to operands for their live ranges
when the live ranges ~~that~~ span [[a]] the function call; and

a tentative register allocator to allocate either [[a]] the scratch register or [[a]] the preserved
register to their respective live ranges when it is unknown ~~that are not immediately~~
~~known~~ whether or not the live ranges ~~they~~ span [[a]] the function call.

35. (Currently amended) A system comprising an integrated compiler to compile a group of
instructions, wherein the integrated compiler comprises:

~~a set of instructions to be compiled; a set of preserved registers capable of storing values that are~~
~~to be preserved across function calls; a set of scratch registers capable to storing values~~
~~that do not need to be preserved across function calls; and an integrated compiler having:~~
an instruction scheduler to~~[[:]]~~ process [[a]] the group of instructions, the instruction scheduler to
further in topological dependence order, and select an instruction to schedule, the
instruction associated with an at least one operand, ~~to schedule~~ the operand comprising a

live range to represent the operational duration of the operand relative to the group of instructions to be processed; and
~~schedule an instruction, if the register allocation was successful; and~~
~~a register allocator to~~[[,]] allocate register to a live range associated with one or more operand,
~~determine if the live range of the operand spans a function call, if so, attempt to allocate a~~
~~preserved register to the operand for its live range when its live range spans a function~~
~~call~~[[,]] and if not, attempt to allocate a scratch register to the operand for its live range
when its live range does not span the function call.

~~[[,]] and if the determination is unknown, treat the live range as tentative.~~

36. (Currently amended) The system of claim 35, wherein the register allocator to further
~~is capable of: determining if the operand's use begins a live range or ends a live range; if the~~
~~operand's use begins a live range, attempting to allocate a register;~~
terminate the attempt to allocate the preserved register or the scratch register to the operand for
its live range when if the operand's use by the selected instruction is to fall at the end of
the ends a live range, and
mark marking the preserved register or the scratch register associated to be allocated to with the
operand as available for reallocation.

37. (Currently amended) The system of claim 35, wherein the register allocator to further
~~is capable of, when attempting to allocate a preserved register: determining if a preserved~~
~~register is available for allocation from a list of previously used preserved registers; and if~~
~~so, allocating~~
allocate the available preserved register to the operand for its for the live range defined by the
operand when the preserved register is in a list of previously used preserved registers to

be marked as available for allocation.

38. (Currently amended) The system of claim 37, wherein the register allocator to further
~~is capable of, if a preserved register is not available from the list of previously used preserved~~
~~registers: attempting~~
attempt to find a tentative live range that includes a second preserved register that is in the list of
previously used preserved registers to be allocated to a tentative live range of a second
operand,[[;]] and if successful, allocating
reallocate the second this preserved register for to the operand for its the live range, defined by
the operand, and
reserve reserving a different preserved register for to the second operand for its the tentative live
range when the attempt to find the second preserved register allocated to the second
operand for its tentative live range is successful.

39. (Currently amended) The system of claim 38, wherein the register allocator to further
~~is capable of, if the attempt to find a tentative live range that includes a preserved register that is~~
~~in the list is not successful: adding~~
add a new preserved register to the list of previously used preserved registers[[;]] and allocating
this
allocate the new preserved register to the operand for its the live range defined by the operand
when the attempt to find the second preserved register allocated to the second operand for
its tentative live range fails.

40. (Currently amended) The system of claim 35, wherein the ~~register allocator is capable of,~~
~~when attempting~~ attempt to allocate [[a]] the scratch register to the operand for its live
range comprises the register allocator to further:

determining if a scratch register is available for allocation; if so, allocating a scratch register for the live range defined by the operand; if not, attempting ~~attempt to steal~~ deallocate a second scratch register from a tentative live range of a second operand live range when the attempt to allocate the scratch register to the operand for its live range fails, marked as tentative; determining if the attempted theft was successful; if so, allocating allocate the stolen second scratch register to the operand for its live range defined by the operand when the second scratch register is successfully deallocated from the second operand for its tentative live range,[[;]] and if not, attempting attempt to allocate [[a]] the preserved register to the operand for its live range when the attempt to deallocate the second scratch register from the second operand for its tentative live range fails.

41. (Currently amended) The system of claim 35, wherein the register allocator to further ~~is capable of, when treating a live range as tentative: if both a scratch register and a preserved register are available for allocation, reserving~~ pre-allocate both the scratch register and the preserved register to the operand for its tentative live range,[[;]] process one or more additional instructions, allowing another instruction to be processed; and wait waiting for more additional information about the tentative live range.

42. (Currently amended) The system of claim 41, wherein the register allocator to further ~~is capable of, when more information is available: if the last use of the live range has been scheduled,~~ receive the additional information about the tentative live range, allocating the reserved scratch

~~register to the live range defined by the operand, and freeing~~
~~deallocate the reserved preserved register from the operand for its tentative live range when the~~
~~last use of the operand for its tentative live range has been scheduled,[[;]] and if a~~
~~function call has been scheduled before the last use of the live range or the reserved~~
~~scratch register has been stolen, allocating the preserved register to the live range defined~~
~~by the operand and freeing~~
~~deallocate the reserved scratch register from the operand for its tentative live range when the~~
~~function call is scheduled before the last use of the operand for its tentative live range or~~
~~when the scratch register is reallocated by any other process.~~

43. (Currently amended) The system of claim 42, wherein the register allocator to further
~~is capable of, when reserving a preserved register for the tentative live range preferring to reserve~~
~~attempt to allocate an [[a]] currently unused preserved register that is in the list of previously~~
~~used preserved registers to the operand for its tentative live range, and before~~
~~attempt to allocate reserving a new unused preserved register to the operand for the its tentative~~
~~live range when the attempt to allocate the unused preserved register to the operand for~~
~~its tentative live range fails.~~

44. (Currently amended) The system of claim ~~[[43]]~~ 41, wherein the register allocator to further
~~is capable of, when treating a live range as tentative: if a scratch register is not available for~~
~~allocation, attempting~~
~~attempt to allocate [[a]] the preserved register to the operand for its tentative live range when the~~
~~scratch register is determined to be unavailable.~~

45. (Currently amended) The system of claim 35, the register allocator to further
~~is capable of: if no proper registers are available for allocation, inserting~~

insert a register spill when the attempt to allocate the preserved register and the attempt to allocate the scratch register to the operand for its live range both fail,[[;]] and either re-attempting re-attempt to allocate the preserved register and the scratch register to the operand for its live range, a register, or selecting another select a second instruction to schedule.

46. (Currently amended) The system of claim 35, wherein the register allocator further comprises includes:

a scratch register allocator to allocate scratch registers to operands for their live ranges when the live ranges that do not span a function call;

a preserved register allocator to allocate preserved registers to operands for their live ranges when the live ranges that span [[a]] the function call; and

a tentative register allocator to allocate either [[a]] the scratch register or [[a]] the preserved register to their respective live ranges when it is unknown that are not immediately known whether or not the live ranges they span [[a]] the function call.